# **OXXYGEN**



Next generation ventilation units easy to install, easy to use

JUST LIKE BREATHING

### Simple, innovative solutions

Who are we and what do we want? What are our guidelines?

Only well-conceived solutions

We are OXYGEN - developers and manufacturers of advanced Lithuanian ventilation systems. Our mission is to ensure a healthy microclimate in every home. We aim to break market stereotypes and offer a superior alternative - smarter, more efficient and more compact products.

Inspired by the European Commission's ambitious strategy for sustainable economic growth, the European Green Deal, together with the KTU University team, we have developed a compact, easy-to-install and easy-to-use heat recovery unit, controlled by a unique energy-saving algorithm.

We offer well-thought-out solutions based on modern technologies and products that are easy to install and user-friendly. With OXYGEN, it's as easy as breathing.



### Healthy home microclimate

### Enthalpy

Forget dry mouths, dry eyes and skin, and hundreds of euros spent on moisturizers. Enthalpy is cutting-edge technology that preserves the humidity in your home, and therefore helps maintain your health.

### Heat and cool recovery

A heat recovery unit is like a fridge that can never be switched off. It is useful in both winter and summer because it efficiently keeps your home warm or cool, saving you money.

### Fresh air and hygiene

Ventilation ensures that air has the right amount of oxygen, eliminating harmful CO2. The filters trap dust, insects and even germs. Rest assured, thanks to the hygienic airflow technology, unwanted kitchen smells are eliminated.



### Tailored to Lithuanian and Nordic climates

### Non-freezing

Your smart heat recovery unit will never freeze. We guarantee uninterrupted ventilation for your home.

### Low costs

Thanks to 5 internal sensors and a unique energy-saving algorithm, you'll conserve heat while ventilating your home, using the minimum amount of electricity.

### High energy efficiency

OXYGEN heat recovery ventilators with advanced plate counterflow heat exchangers are suitable for even the highest energy class A++. Save up to 93% energy.



### Easy to install

### Everything is included

The electric heater, control automation and other necessary components are located inside the unit, eliminating the time and cost of installing external ventilation accessories and reducing the space required to install the heat recovery unit.

### Lightweight

The compact and ultra-lightweight OXYGEN heat recovery unit housing is made of EPP material with excellent thermal and acoustic insulation properties. Installing OXYGEN products alone is fast and easy.

### Smart control

Enjoy all the smart features by controlling the heat recovery unit via the app or the color LCD touchscreen control panel.





### Comfort features

### Bathroom mode

Press the auxiliary switch together with the light switch to activate the increased ventilation mode and the heat recovery unit will remove steam and unwanted odors.

### Hood mode

Activate the enhanced ventilation mode while cooking. When coupled to the extractor fan, the heat recovery unit will extract vapors and unwanted odors.

### Summer ventilation

Enjoy fresh air in summer by opening your windows, and entrust the heat recovery unit with the ventilation of bathrooms, kitchens and other enclosed spaces.



## Easy to use

### Iconic color

Oxygen Elemental is an iconic color that embodies the fundamental building block of life—oxygen element itself. With its vibrant turquoise hue, it highlights the natural and scientific connection to breathable air, merging the essence of nature with cutting-edge innovation.

### Easy maintenance

Easily replace the filters by opening the filter covers. OXYGEN heat recovery units no longer require any servicing.

### An invisible helper

The heat recovery unit will adapt to your lifestyle – a weekly ventilation program will give you extra comfort every day.









Smart Ceiling Mounted Heat Recovery Unit

# Just like breathing

Next generation smart non-freezing ventilation units easy to install, easy to use



### Intelligent control that helps you breathe easier With the powerful Amazon Web Service cloud solution













**OXYGEN** easy cloud

History of use

SKU	Product
P000127	Easy C150 right
P000129	Easy C150 left
P000128	Easy C150 right with integrated CO2 sensor*
P000130	Easy C150 left with integrated CO2 sensor*
P000004	Easy control panel with Wifi and Bluetooth white
P000176	Easy control panel with Wifi and Bluetooth black
P000182	LCD SimpleTouch control with Wifi and Bluetooth white
P000005	LCD SimpleTouch control with Wifi and Bluetooth black













Quiet

management





Energy


EcoDesign


Integrated CO2


# OXYGEN

### **Technical specification**

Cold climate	kWh/m².a	-83.5
Average climate	kWh/m².a	-43.3
Warm climate	kWh/m².a	-13.0
Declared typology		Bi-directional, residential ventilatio
Type of drive installed or intended to be		Variable speed drive
Type of heat recovery system		Recuperative
Thermal efficiency of heat recovery	%	93
Maximum flow rate	m³/h	143
Electric power input of the fan drive, including	W	76
Sound power level (LWA)	dB	49
Reference flow rate	m³/s	0.028
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m³/h)	0.29
Control factor		0.65
Control typology		Local demand control
Declared maximum leakage rate:		
Internal	%	1.4
External	%	2.5
The annual electricity consumption (AEC)	kWh/100m².a	373
The annual heating saved (AHS)		
Cold climate	kWh/100m².a	9172
Average climate	kWh/100m².a	4689
Warm climate	kWh/100m².a	2120
Integrated adaptive pre-heater	W	800
Power supply		230V, 50Hz, 5A
Dimensions	mm	1015 x 537 x 272
Weight	kg	24
Color		Oxygen Elemental







# EASY C150E



Smart Ceiling Mounted Heat Recovery Unit With Enthalpy

# Just like breathing

Next generation smart non-freezing ventilation units easy to install, easy to use



### Intelligent control that helps you breathe easier With the powerful Amazon Web Service cloud solution









LCD SimpleTouch



OXYGEN easy app



**OXYGEN** easy cloud



History of use

SKU	Product
P000131	Easy C150E enthalpy right
P000133	Easy C150E enthalpy left
P000132	Easy C150E enthalpy right with integrated CO2 sensor*
P000134	Easy C150E enthalpy left with integrated CO2 sensor*
P000004	Easy control panel with Wifi and Bluetooth white
P000176	Easy control panel with Wifi and Bluetooth black
P000182	LCD SimpleTouch control with Wifi and Bluetooth white
P000005	LCD SimpleTouch control with Wifi and Bluetooth black



Compact





Easy to

Energy





Moisture

Smart management



EcoDesign




Integrated CO2


# EASY C150E


# 

### **Technical specification**

Cold climate	kWh/m².a	-82.0
Average climate	kWh/m².a	-42.9
Warm climate	kWh/m².a	-17.9
Declared typology		Bi-directional, residential ventilatio
Type of drive installed or intended to be		Variable speed drive
Type of heat recovery system		Recuperative
Thermal efficiency of heat recovery	%	87.9
Maximum flow rate	m³/h	143
Electric power input of the fan drive, including	W	76
Sound power level (LWA)	dB	49
Reference flow rate	m³/s	0.028
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m³/h)	0.24
Control factor		0.65
Control typology		Local demand control
Declared maximum leakage rate:		
Internal	%	1.4
External	%	2.5
The annual electricity consumption (AEC)	kWh/100m².a	172
The annual heating saved (AHS)		
Cold climate	kWh/100m².a	9096
Average climate	kWh/100m².a	4650
Warm climate	kWh/100m².a	2103
Integrated adaptive pre-heater	W	800
Power supply		230V, 50Hz, 5A
Dimensions	mm	1015 x 539 x 273
Weight	kg	25
Color		Oxygen Elemental









Smart Ceiling Mounted Heat Recovery Unit

# Just like breathing

Next generation smart non-freezing ventilation units easy to install, easy to use



### Intelligent control that helps you breathe easier With the powerful Amazon Web Service cloud solution









LCD SimpleTouch



OXYGEN easy app



**OXYGEN** easy cloud



History of use

SKU	Product
P000135	Easy C200 right
P000137	Easy C200 left
P000136	Easy C200 right with integrated CO2 sensor*
P000138	Easy C200 left with integrated CO2 sensor*
P000004	Easy control panel with Wifi and Bluetooth white
P000176	Easy control panel with Wifi and Bluetooth black
P000182	LCD SimpleTouch control with Wifi and Bluetooth white
P000005	LCD SimpleTouch control with Wifi and Bluetooth black



Compact



Easy to





Quiet

management



Energy




EcoDesign


Integrated CO2


# **O**XYGEN

### **Technical specification**

Cold climate	kWh/m².a	-81.6
Average climate	kWh/m².a	-42.0
Warm climate	kWh/m².a	-16.8
Declared typology		Bi-directional, residential ventilation
Type of drive installed or intended to be		Variable speed drive
Type of heat recovery system		Recuperative
Thermal efficiency of heat recovery	%	90
Maximum flow rate	m³/h	200
Electric power input of the fan drive, including	W	110
Sound power level (LWA)	dB	49
Reference flow rate	m³/s	0.039
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m <sup>3</sup> /h)	0.34
Control factor		0.65
Control typology		Local demand control
Declared maximum leakage rate:		
Internal	%	1.4
External	%	2.5
The annual electricity consumption (AEC)	kWh/100m².a	223
The annual heating saved (AHS)		
Cold climate	kWh/100m².a	9182
Average climate	kWh/100m².a	4693
Warm climate	kWh/100m².a	2122
Integrated adaptive pre-heater	W	800
Power supply		230V, 50Hz, 5A
Dimensions	mm	1015 x 537 x 272
Weight	kg	24
Color		Oxygen Elemental







# EASY C200E



Smart Ceiling Mounted Heat Recovery Unit With Enthalpy

# Just like breathing


Next generation smart non-freezing ventilation units easy to install, easy to use



### Intelligent control that helps you breathe easier With the powerful Amazon Web Service cloud solution









LCD SimpleTouch



OXYGEN easy app



**OXYGEN** easy cloud



History of use

SKU	Product
P000115	Easy C200E enthalpy right
P000141	Easy C200E enthalpy left
P000140	Easy C200E enthalpy right with integrated CO2 sensor*
P000142	Easy C200E enthalpy left with integrated CO2 sensor*
P000004	Easy control panel with Wifi and Bluetooth white
P000176	Easy control panel with Wifi and Bluetooth black
P000182	LCD SimpleTouch control with Wifi and Bluetooth white
P000005	LCD SimpleTouch control with Wifi and Bluetooth black



Compact



Easy to

Energy





management







EcoDesign


Integrated CO2


# EASY C200E


# **O**XYGEN

### **Technical specification**

Cold climate	kWh/m².a	-77.3
Average climate	kWh/m².a	-39.6
Warm climate	kWh/m².a	-15.4
Declared typology		Bi-directional, residential ventilatio
Type of drive installed or intended to be		Variable speed drive
Type of heat recovery system		Recuperative
Thermal efficiency of heat recovery	%	80.8
Maximum flow rate	m³/h	200
Electric power input of the fan drive, including	W	110
Sound power level (LWA)	dB	49
Reference flow rate	m³/s	0.039
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m³/h)	0.38
Control factor		0.65
Control typology		Local demand control
Declared maximum leakage rate:		
Internal	%	1.4
External	%	2.5
The annual electricity consumption (AEC)	kWh/100m².a	245
The annual heating saved (AHS)		
Cold climate	kWh/100m².a	8809
Average climate	kWh/100m².a	4503
Warm climate	kWh/100m².a	2036
Integrated adaptive pre-heater	W	800
Power supply		230V, 50Hz, 5A
Dimensions	mm	1015 x 537 x 272
Weight	kg	25
Color		Oxygen Elemental









Smart Ceiling Mounted Heat Recovery Unit

# Just like breathing

Next generation smart non-freezing ventilation units easy to install, easy to use



### Intelligent control that helps you breathe easier With the powerful Amazon Web Service cloud solution









LCD SimpleTouch



OXYGEN easy app



**OXYGEN** easy cloud



History of use

SKU	Product
P000143	Easy C250 right
P000145	Easy C250 left
P000144	Easy C250 right with integrated CO2 sensor*
P000146	Easy C250 left with integrated CO2 sensor*
P000004	Easy control panel with Wifi and Bluetooth white
P000176	Easy control panel with Wifi and Bluetooth black
P000182	LCD SimpleTouch control with Wifi and Bluetooth white
P000005	LCD SimpleTouch control with Wifi and Bluetooth black



Compact





Easy to





management



Energy




Integrated CO2


Quiet


# 

### **Technical specification**

Cold climate	kWh/m².a	-84.5
Average climate	kWh/m².a	-41.6
Warm climate	kWh/m².a	-17.0
Declared typology		Bi-directional, residential ventilatio
Type of drive installed or intended to be		Variable speed drive
Type of heat recovery system		Recuperative
Thermal efficiency of heat recovery	%	80.3
Maximum flow rate	m³/h	243
Electric power input of the fan drive, including	W	106
Sound power level (LWA)	dB	49
Reference flow rate	m³/s	0.047
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m <sup>3</sup> /h)	0.25
Control factor		0.65
Control typology		Local demand control
Declared maximum leakage rate:		
Internal	%	1.4
External	%	2.5
The annual electricity consumption (AEC)	kWh/100m².a	130
The annual heating saved (AHS)		
Cold climate	kWh/100m².a	8790
Average climate	kWh/100m².a	4490
Warm climate	kWh/100m².a	2030
Integrated adaptive pre-heater	W	800
Power supply		230V, 50Hz, 5A
Dimensions	mm	1015 x 539 x 273
Weight	kg	24
Color		Oxygen Elemental







# EASY C250E



Smart Ceiling Mounted Heat Recovery Unit With Enthalpy

# Just like breathing

Next generation smart non-freezing ventilation units easy to install, easy to use



### Intelligent control that helps you breathe easier With the powerful Amazon Web Service cloud solution









LCD SimpleTouch



OXYGEN easy app



**OXYGEN** easy cloud



History of use

SKU	Product
P000209	Easy C250E right
P000223	Easy C250E left
P000227	Easy C250E right with integrated CO2 sensor*
P000226	Easy C250E left with integrated CO2 sensor*
P000004	Easy control panel with Wifi and Bluetooth white
P000176	Easy control panel with Wifi and Bluetooth black
P000182	LCD SimpleTouch control with Wifi and Bluetooth white
P000005	LCD SimpleTouch control with Wifi and Bluetooth black



Compact



Easy to





Smart management





Energy



EcoDesign




Integrated CO2


# EASY C250E


# OXYGEN

### **Technical specification**

Cold climate	kWh/m².a	-75.2
Average climate	kWh/m².a	-38.2
Warm climate	kWh/m².a	-14.4
Declared typology		Bi-directional, residential ventilatio
Type of drive installed or intended to be		Variable speed drive
Type of heat recovery system		Recuperative
Thermal efficiency of heat recovery	%	77.3
Maximum flow rate	m³/h	240
Electric power input of the fan drive, including	W	142.8
Sound power level (LWA)	dB	48
Reference flow rate	m³/s	0.046
Reference pressure difference	Pa	50
Specific power input (SPI)	W/(m <sup>3</sup> /h)	0.42
Control factor		0.65
Control typology		Local demand control
Declared maximum leakage rate:		
Internal	%	2.07
External	%	0.2
The annual electricity consumption (AEC)	kWh/100m².a	267
The annual heating saved (AHS)		
Cold climate	kWh/100m².a	8655
Average climate	kWh/100m².a	4424
Warm climate	kWh/100m².a	2001
Integrated adaptive pre-heater	W	800
Power supply		230V, 50Hz, 5A
Dimensions	mm	1015 x 537 x 272
Weight	kg	25
Color		Oxygen Elemental









### Heat recovery unit = health

A ventilation unit is an investment in your health. By having a smart ventilation system at home, you can create healthier living conditions. Why is clean air so important for the human body?

### Heat recovery unit as a cure for diseases

Poor sleep, fatigue or inability to concentrate - these problems are often caused by poor indoor air quality. Ensuring that fresh air is constantly circulating in your home is a big step towards a healthy home microclimate.

Ventilation unit protect against:















### Sustainability

The European Commission's strategy for sustainable growth - the European Green Deal - envisages energy-efficient and, in the future, passive houses. Perhaps the most important element of such homes is the heat recovery system. A recuperator is a sustainable product that reduces our CO2 footprint while conserving energy. Breathe eco-friendly air.

### Intelligent control that helps you breathe easier



Easy panels



LCD SimpleTouch



**OXYGEN** easy app



**OXYGEN** easy cloud



History of use

With the powerful Amazon Web Service cloud solution





# No more headaches for property developers

Developing real estate? Don't get lost in the confusing world of ventilation systems. OXYGEN breaks the established rules, offering simplicity, efficiency and progress. By consulting OXYGEN at the very beginning of your project, you will not only avoid mistakes, but also save money.

The right heat recovery unit will reduce the cost of building insulation and allow you to achieve a higher energy performance class. And a good quality ventilation unit will make a buyer's decision much easier.

# Installers are OXYGEN's true ambassadors

It has never been easier for installers. Installing an OXYGEN heat recovery unit alone is easier and up to 2 times faster. The electric heater, control automation and other necessary components are located inside, so you won't have to spend time installing external accessories and you'll need less space to install the heat recovery unit.


In cooperation with OXYGEN, increase your knowledge and gain practical experience at the Easy Academy training sessions, where we share best practices, present the latest news from the ventilation world and advise on all ventilation issues.




# Beautiful and easy-to-choose solutions for architects and designers

Follow the example of western markets and choose the most advanced OXYGEN heat recovery units for your projects.

We provide assistance, advice and expert project evaluations. We share supporting CAD, 3D-model and specification files. After all, simplicity and elegance are key.



OXYGEN solutions are both convenient and easy to understand when choosing, buying or using ventilation equipment. With OXYGEN, it's as easy as breathing.





### Finally, beautiful panels

Elegant panels are equipped with both WiFi and Bluetooth. Along with the panels, customers gain access to the OXYGEN Easy App and the OXYGEN Easy Cloud platform, enabling control from anywhere in the world.

# Control from anywhere

The new OXYGEN Easy models can be conveniently controlled from anywhere in the world using the OXYGEN Easy App (available for iOS and Android) and the OXYGEN Easy Cloud platform.



# Selected device Device: Internet gateway 1005884110 OKYGEN assy installation process Indernet gateway settings OWYGEN arms OWYGEN CONTROLL OWYGEN ARMS OWYGEN OW

# Balancing via Bluetooth 8

Installers can now effortlessly perform the startup and balancing of the ventilation unit via Bluetooth using the OXYGEN Installer App. This mobile application works without an internet connection, which is often unavailable at installation sites during ventilation system setup.

### Data Chart

Easily review the usage history of the unit with detailed information provided by 5 sensors.





Specific energy consumption (SEC), SEC class							
Cold climate	kWh/m².a	-83.5	-82.0	-81.6	-77.3	-84.5	-75.2
Average climate	kWh/m².a	-43.3	-42.9	-42.0	-39.6	-41.6	-38.2
Warm climate	kWh/m².a	-13.0	-17.9	-16.8	-15.4	-17.0	-14.4
Thermal efficiency of heat recovery	%	93	87.9	06	80.8	80.3	77.3
Type of heat recovery system		Counter-flow	Enthalpy	Counter-flow	Enthalpy	Counter-flow	Enthalpy
Maximum flow rate	m³/h	143	143	200	200	243	240
Suitable up to:	m²	80	80	001	100	120	120
Electric power input of the fan drive, including	M	76	76	011	011	106	142.8
Sound power level (LWA)	dB	64	64	67	67	67	48
Reference flow rate	m³/s	0.028	0.028	0.039	0.039	0.047	0.046
Reference pressure difference	Ра	50	50	50	50	50	50
Specific power input (SPI)	W/(m³/h)	0.29	0.24	0.34	0.38	0.25	0.42
Control factor		0.65	0.65	0.65	0.65	0.65	0.65
Declared maximum leakage rate:							
Internal	%	1.4	1.4	1.4	1.4	1.4	2.07
External	%	2.5	2.5	2.5	2.5	2.5	0.2
The annual electricity consumption (AEC)	kWh/100m².a	373	172	223	245	130	267
The annual heating saved, (AHS)							
Cold climate	kWh/100m².a	9172	9606	9182	8809	8790	8655
Average climate	kWh/100m².a	4689	4650	4693	4503	4490	4424
Warm climate	kWh/100m².a	2120	2103	2122	2036	2030	2001
Integrated adaptive pre-heater	Λ	800	800	800	800	800	800
Power supply				230V, 50Hz, 5A			
Dimensions	mm		,	1015 x 537 x 272			
Weight	kg	24	25	24	25	24	25
Color			0	Oxygen Elemental			

# Users download OXYGEN Easy app









# Installers download OXYGEN Installer app









The contents of this catalog are subjected to change without prior notice. Every possible effort has been made to ensure that the data herein is correct. However, OXYGEN group cannot assume any liability for any direct, in director consequential damages arising from the use of the information specified here.

**OXY 1/25/EN**